



## **Frimstone Ltd**

### **CPR Declaration of Performance (DoP)**

**DoP reference:**

A38 DOP

**1. Unique identification code of the product type (in combination with point 2):**

BS EN 12620:2002+A1:2008 Aggregates for Concrete

**2. Identification of the construction product:**

Cambridge 0/2 Concrete Sand

**3. Intended use:**

BS EN 12620:2002+A1:2008

Preparation for concrete for use in buildings, roads and other civil engineering works

**4. Company name:**

Frimstone Ltd  
Ashcraft Farm,  
Crimplesham,  
Norfolk,  
PE33 9EB

**5. Authorised representative:**

Keith Porter (address as above)

**6. System of assessment:**

Attestation Level 4

**7. Standard and notified body:**

Not applicable. Attestation Level 4

**8. European Technical Assessment (ETA):**

Not applicable

continued...

## 9. Declared performance:

| Essential Characteristics  | Declared values  | Test method  |
|--|--|--|
| Aggregate size   | 0/2  | Designation as section 4.2 BS EN 12620:2002+A1:2008  |
| Grading  | Gf85   | EN 933-1, Section 4.3 Tables 2-7 (EN 12620)  |
| Shape of coarse aggregate  | Not applicable   | EN 933-3, Section 4.4 Tables 8 or 9 (EN 12620)   |
| Particle density   | NPD  | EN 1097-6  |
| Water absorption   | NPD  | EN 1097-6  |
| Shell content of coarse aggregate  | Not applicable   | EN 1367-1/EN 1367-2, Section 5.7.1 Table 18 (EN 12620)   |
| Resistance to fragmentation of coarse aggregate  | Not applicable   | EN 1097-2, clause 5 or 6, Section 5.2 Table 12 or 13 (EN 12620)  |
| Resistance to wear of coarse aggregate   | Not applicable   | EN 1097-1, Section 5.3 Table 14 (EN 12620)   |
| Resistance to polishing  | NPD  | EN 1097-8, Section 5.4.1 Table 15 (EN 12620)   |
| Resistance to surface abrasion   | NPD  | EN 1097-8, Annex A, Section 5.4.2 Table 16 (EN 12620)  |
| Resistance to abrasion from studded tyres  | NPD  | EN 1097-9, Section 5.4.2 Table 17 (EN 12620)   |
| Constituents of coarse recycled aggregate  | Not applicable   | prEN 933-11, Section 5.8 Table 20 (EN 12620)   |
| Chlorides  | Water soluble <0.01%   | EN 1744-1, clause 7 (water) and/or EN 1744-5 (acid if requested)   |
| Acid soluble sulfates  | AS <sub>0.8</sub> (<0.08%)   | EN 1744-1, clause 12, Section 6.3.1 Table 21 (EN 12620)  |
| Total sulfur   | <1% S  | EN 1744-1, clause 11, Section 6.3.2 (EN 12620)   |
| Water soluble sulfate content of recycled aggregate  | Not applicable. Natural Aggregate.   | EN 1744-1, clause 12, Section 6.3.3 Table 22 (EN 12620)  |
| Constituents of natural aggregates which alter the rate of setting and hardening of concrete | No organic substances (< clause a & b)   | EN 1744-1, clause 5.1 (presence of organic matter) & Clause 5.3 (effect), Section 6.4.1, clause a & b (EN 12620) |
| Influence of initial setting time of cement (recycle aggregates)                             | Not applicable. Natural Aggregate.   | EN 1744-6, Section 6.4.1, Table 23 (EN 12620)  |
| Carbonate content of fine aggregate for concrete pavement surface courses                    | Not Applicable. Coarse Aggregate.  | EN 196-2, clause 5   |
| Volume stability - drying shrinkage  | <0.075%  | EN 1367-4  |
| Constituents which affect the volume stability of air-cooled blastfurnace slag               | Not applicable. Not air-cooled blastfurnace slag aggregate.  | EN 1744-1, clause 19.1 & 19.2  |
| Freeze/thaw resistance of coarse aggregate   | Not applicable   | EN 1367-1 or EN 1367-2, Section 5.7.1, Tables 18 or 19 (EN 12620)  |
| Alkali-silica reactivity   | NPD  | CEN CR 1901  |
| Dangerous Substances   | Regulatory Information: Not classified as dangerous. Consideration of the following risk & safety phrases is recommended: Risk Phrases: R36/37 - Irritating to eyes and respiratory system. Safety Phrases: S36/ 37/ 39 - Wear suitable protective clothing, gloves and eye /face protection. Inhalation: If inhaled over a prolonged or extended period, respirable dust from natural aggregate can lead to respiratory system damage and disease. Respirable crystalline silica has been associated with the lung disease silicosis. Skin Contact: Prolonged contact with skin may cause irritation and dryness, which may lead to dermatitis. Eye Contact: Particles of grit or dust from natural aggregates may irritate and scratch eyes. Ingestion: Unlikely to cause any problems | Not Dangerous. ZA.1. Council Directive 76/769/EEC  |
| Declaration of Performance   | In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="http://www.frimstone.co.uk/aggregates.php">http://www.frimstone.co.uk/aggregates.php</a> . The appropriate DoP is referenced A38 DOP on the CE Regulations page.   | CPR DoP Electronic Provision No. 305/2011  |


## 10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Mr Keith Porter (Sales Manager), issued at the address given in point 4, 01 Jan 2019.

Signature: *Keith Porter*

## Supporting information:

The CE Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement or invoice (delivered either in hard-copy or electronic format within an email).

| <br>19              |   | <b>BS EN 12620:2002+A1:2008</b>  | <b>CE Mark ref. A38 Dated 01 Jan 2019</b>                |
|--|---|--|--|
| <b>Aggregates for concrete</b>   |   |  |  |
| <b>Frimstone Ltd</b>   |   |  |  |
| <b>Ashcraft Farm, Crimpleham, Norfolk, PE33 9EB</b>  |   |  |  |
| <b>Source quarry and material description: Cambridge 0/2 Concreting Sand</b>                         |   |  |  |
| Intended use: Preparation for concrete for use in buildings, roads and other civil engineering works |   |  |  |
| Attestation Level 4  |   |  |  |
| Essential Characteristics  | Declared values   | Test method  |  |
| Aggregate size   | 0/2   | Designation as section 4.2 BS EN 12620:2002+A1:2008  |  |
| Grading  | Gf85  | EN 933-1, Section 4.3 Tables 2-7 (EN 12620)  |  |
| Shape of coarse aggregate  | Not applicable  | EN 933-3, Section 4.4 Tables 8 or 9 (EN 12620)   |  |
| Particle density   | NPD   | EN 1097-6  |  |
| Water absorption   | NPD   | EN 1097-6  |  |
| Shell content of coarse aggregate  | Not applicable  | EN 1367-1/EN 1367-2, Section 5.7.1 Table 18 (EN 12620)   |  |
| Resistance to fragmentation of coarse aggregate  | Not applicable  | EN 1097-2, clause 5 or 6, Section 5.2 Table 12 or 13 (EN 12620)  |  |
| Resistance to wear of coarse aggregate   | Not applicable  | EN 1097-1, Section 5.3 Table 14 (EN 12620)   |  |
| Resistance to polishing  | NPD   | EN 1097-8, Section 5.4.1 Table 15 (EN 12620)   |  |
| Resistance to surface abrasion   | NPD   | EN 1097-8, Annex A, Section 5.4.2 Table 16 (EN 12620)  |  |
| Resistance to abrasion from studded tyres  | NPD   | EN 1097-9, Section 5.4.2 Table 17 (EN 12620)   |  |
| Constituents of coarse recycled aggregate  | Not applicable  | prEN 933-11, Section 5.8 Table 20 (EN 12620)   |  |
| Chlorides  | Water soluble <0.01%  | EN 1744-1, clause 7 (water) and/or EN 1744-5 (acid if requested)   |  |
| Acid soluble sulfates  | AS <sub>0.8</sub> (<0.8%)   | EN 1744-1, clause 12, Section 6.3.1 Table 21 (EN 12620)  |  |
| Total sulfur   | <1% S   | EN 1744-1, clause 11, Section 6.3.2 (EN 12620)   |  |
| Water soluble sulfate content of recycled aggregate  | Not applicable. Natural Aggregate.  | EN 1744-1, clause 12, Section 6.3.3 Table 22 (EN 12620)  |  |
| Constituents of natural aggregates which alter the rate of setting and hardening of concrete         | No organic substances (< clause a & b)  | EN 1744-1, clause 15.1 (presence of organic matter) & Clause 15.3 (effort), Section 6.4.1, clause a & b (EN 12620) |  |
| Influence of initial setting time of cement (recycle aggregates)                                     | Not applicable. Natural Aggregate.  | EN 1744-6, Section 6.4.1, Table 23 (EN 12620)  |  |
| Carbonate content of fine aggregate for concrete pavement surface courses                            | Not Applicable. Coarse Aggregate.   | EN 196-2, clause 5   |  |
| Volume stability - drying shrinkage  | <0.075%   | EN 1367-4  |  |
| Constituents which affect the volume stability of air-cooled blastfurnace slag                       | Not applicable. Not air-cooled blastfurnace slag aggregate.   | EN 1744-1, clause 19.1 & 19.2  |  |
| Freeze/thaw resistance of coarse aggregate   | Not applicable  | EN 1367-1 or EN 1367-2, Section 5.7.1, Tables 18 or 19 (EN 12620)  |  |
| Alkali-silica reactivity   | NPD   | CEN CR 1901  |  |
| Dangerous Substances   | <small>Regulatory Information. Not classified as dangerous. Consideration of the following risk &amp; safety phrases is recommended: Risk Phrases: R36/37 - Irritating to eyes and respiratory system. Safety Phrases: S36/ 37/ 39 - Wear suitable protective clothing, gloves and eye /face protection. Inhalation: If inhaled over a prolonged or extended period, respirable dust from natural aggregate can lead to respiratory system damage and disease. Respirable crystalline silica has been associated with the lung disease silicosis. Skin Contact: Prolonged contact with skin may cause irritation and dryness, which may lead to dermatitis. Eye Contact: Particles of grit or dust from natural aggregates may irritate and scratch eyes. Ingestion: Unlikely to cause any problems</small> |  | <b>Not Dangerous. ZA.1. Council Directive 76/769/EEC</b> |
| Declaration of Performance   | <small>In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="http://www.frimstone.co.uk/aggregates.php">http://www.frimstone.co.uk/aggregates.php</a>. The appropriate DoP is referenced A38 DOP on the CE Regulations page.</small>  |  | <b>CPR DoP Electronic Provision No. 305/2011</b>         |

Please contact us should you require any further information.